

PDF Serial Eeprom Cross Reference Guide PDF Book is the book you are looking for, by download PDF Serial Eeprom Cross Reference Guide book you are also motivated to search from other sources

### **Serial EEPROM Cross Reference Guide**

SERIAL EEPROM CROSS REFERENCE GUIDE Size (bits) MCHP Part # Atmel Part # Catalyst Part # Fairchild Part # Philips / Signetics Part # Rohm Part # ST Part # Xicor Part # 128 To 1024K I2C™ Devices (Microchip's B Revision Devices Do Not Use Address Pins A0, A1 And A2. These Pins Have No 1th, 2024

### **EEPROM Cross Reference List**

AT93 Atmel Non-Volatile Memory, 3-wire Serial Bus Interface C C = CMOS XX 46 = 1K, 56 = 2K, 57 = 2K With Shorter Address, 66 = 4K Blank/A/C Blank = X8 Or X16 Organization, A = X16 Org., C = X16 Org. With Schmitt Trigger Inputs Blank/R/W Blank = Normal Pin Out, R = Rotated Die P 3th, 2024

### **1-Mbit Serial I<sup>2</sup>C Bus EEPROM - STMicroelectronics**

Description M24M01-R M24M01-DF 6/47 DocID12943 Rev 14 1 Description The M24M01 Is A 1 Mbit I2C-compatible EEPROM (Electrically Erasable PROgrammable

Memory) Organized As 128 K × 8 Bits. The M24M01-R Can Operate With 3th, 2024

### **32-Kbit Serial SPI Bus EEPROM With High-speed Clock**

See Section 10: Package Information For Package Dimensions, And How To Identify Pin-1. 633 \$ # 1 (/,\$ 36## 7!) \$- XXX Memory Organization M95320-W M95320-R M95320-DF 8/48 DocID5711 Rev 16 2 Memory Organization The Memory Is Organized As Shown In The Following Figure. Figure 3. Block Diagram 06 2th, 2024

### **1K Microwire Compatible Serial EEPROM**

© 2002-2013 Microchip Technology Inc. Ds20001749k-page 5 93aa46a/b/c, 93lc46a/b/c, 93c46a/b/c Figure 1-1: Synchronous Data Timing Table 1-3: Instructio 1th, 2024

### **Basic Serial EEPROM Operation**

Microchip's Default Conditions For The 3-wire And 2-wire Serial EEPROMs To Allow The System Designer To Utilize The Benefits Of Serial EEPROMs. 3-WIRE BUS OPERATION PRIMER Many Serial EEPROM Data Sheets Are Written In A Conventional Memory Data Sheet Format Which Empha-sizes The Featu 2th, 2024

### **Supervisory Circuits With EEPROM Serial 16-Kb I2C ...**

With Brown Out Protection And A Watchdog Timer Are Integrated Together In Low Power CMOS Technology. Memory Interface Is Via An I2C Bus. The 1.6-second Watchdog Circuit Returns A System To A Known Good State If A Software Or Hardware Glitch Halts Or “hangs” The System. The CAT1161 Watchdog Monitors The SDA Line, Making An Additional PC Board Trace Unnecessary. The Lower Cost CAT1162 Does Not Have A Watchdog Timer. The Power S 2th, 2024

### **Supervisory Circuits With I2C Serial CMOS EEPROM ...**

The 1.6-second Watchdog Circuit Returns A System To A Known Good State If A Software Or Hardware Glitch Halts Or “hangs” The System. The CAT1161 Watchdog Monitors The SDA Line, Making An Additional PC Board Trace Unnecessary. The Lower Cost CAT1162 Does Not Have A Watchdog Timer. The Power S 2th, 2024

### **Two-wire Serial EEPROM**

Note: 1.  $V_{IL}$  Min And  $V_{IH}$  Max Are Reference Only And Are Not Tested. Table 2-1. Pin Capacitance(1) Applicable Over Recommended Operating Range From  $T_A = 25^\circ\text{C}$ ,  $f = 1.0\text{ MHz}$ ,  $V_{CC} = +1.8\text{V}$  Symbol Test Condition Max Units Conditions C I/O Input/Output Capacitance (SDA) 8 PF  $V_{I/O} = 0\text{V}$  C IN Input Capacitance ( $A_0, A_1, A$

2, SCL) 6 PF V IN = 0V ... 2th, 2024

### **64K SPI Bus Serial EEPROM - Arrow**

0.7 V CC V CC +1 V D002 V IL 1 Low-level Input Voltage-0.3 0.3 V CC VVCC T 2.7V  
D003 V IL 2-0.3 0.2 V CC VVCC

### **25AA640A/25LC640A 64K SPI Bus Serial EEPROM Data Sheet - ...**

Feb 28, 2020 · 25AA640A/25LC640A DS20001830G-page 4 2003-2021 Microchip  
Technology Inc. 16 THS HOLD Setup Time 20 — Ns 4.5V Vcc 5.5V 40 — Ns 2.5V Vcc  
4.5V 3th, 2024

### **4K SPI Bus Serial EEPROM - Arrow**

D002 VIH2 0.7 VCC VCC+1 V VCC

### **256 I2C CMOS Serial EEPROM - Massachusetts Institute Of ...**

Industrial (I): V. CC = +1.8 V To 5.5 V T. AMB = -40°C To +85°C Automotive (E): V.  
CC = +2.5 V To 5.5 V T. AMB = -40°C To +125°C. Param. No. Sym Characteristic  
Min Max Units Conditions. D1 — A0, A1, A2, SCL, SDA And WP Pins: — — D2 V.  
IH. High Level Input Voltage 0.7 V. CC —V— D3 V. IL. Low Level Input Voltage — 0.3  
V. CC ... 1th, 2024

## **Serial Eeprom Rohm - Cgm.lbs.com.my**

45K7354. Eaton Cutler-Hammer Type BR Breaker 55A/2 Pole 120/240V 10K  
Integrated Circuits (ICs) | Memory | DigiKey Co-Browse. By Using The Co-Browse  
Feature, You Are Agreeing To Allow A Support Representative From Digi-Key To  
View Your Browser Remotely. When The Co-Browse Window Opens, Give 2th, 2024

## **Printer Cross Reference Laser Printer Cross Reference May ...**

Jun 01, 2018 · Click On The Model To Get The Product Brochure. ... Xerox R # Xerox  
R # Xerox R # Xerox R # Xerox R # Xerox R # CQ 8700 14 P 5550 10 VL B400 7 VL  
B615 2 VL C605 (17) WC 3655 1 ... P 4622 8. RI 1th, 2024

## **CROSS REFERENCE FOR APRILIA & BMW CROSS-REFERENCE ...**

CROSS-REFERENCE CROSS-REFERENCE CROSS-REFERENCE 1208 STREET • TUCKER  
ROCKY ... FRONT TIRE . REAR TIRE : CHAIN/ SIZE : FRONT SPROCKET : REAR  
SPROCKET : BATTERY : NGK SPARK PLUG : Rally 50 AIR (95-04) 120/90x10 ;  
120/90x10 : Belt : None : None : YB4L-B : BR7HS : RS50 Replica (99-06) 90/80x17 ...  
BR9ES : Scarabeo 100 (07-08) 2.50x16 ; 2.75x16 ... 2th, 2024

## **PIC16F84A 18-pin Enhanced Flash/EEPROM 8-Bit MCU Data Sheet**

Devices Included In This Data Sheet: • PIC16F84A • Extended Voltage Range Device Available (PIC16 LF 84A) High Performance RISC CPU Features: • Only 35 Single Word Instructions To Learn • All Instructions Single Cycle Except For Program Branches Which Are Two-cycle • Operating Speed: DC - 20 MHz Clock Input DC - 200 Ns Instruction Cycle 1th, 2024

## **PIC16F8X, 18-Pin FLASH/EEPROM 8-Bit MCU Data Sheet**

Identification System” At The Back Of This Data Sheet To Specify The Correct Part Number. There Are Four Device “types” As Indicated In The Device Number. 1. F, As In PIC16F84. These Devices Have Flash Program Memory And Operate Over The Standard Voltage Range. 2. LF, As In PIC16 LF84. 3th, 2024

## **PIC16F84A 18-pin Enhanced Flash/EEPROM 8-Bit MCU Data ...**

Data EEPROM Memory Have The Address Range 0h-3Fh. More Details On The EEPROM Memory Can Be Found In Section 5.0. Additional Information On Device Memory May Be Found In The PICmicro™ Mid-Range Reference Manual, (DS33023).

2.1 Program Memory Organization The PIC16FXX Has A 13-bit Program Counter Capable Of 1th, 2024

### **ROM, EPROM, And EEPROM Technology**

Of ROM Architectures (NOR, NAND, Etc.) Are Detailed In The Flash Memory Section (Section 10) As They Use The Same Principle. Figure 9-3 Shows An Array Of Storage Cells (NAND Architecture). This Array Consist 2th, 2024

### **18-pin Flash/EEPROM 8-Bit Microcontrollers**

Contact Your Microchip Regional Sales Office. 2.4 ROM Devices Some Of Microchip's Devices Have A Corresponding Device Where The Program Memory Is A ROM. These Devices Give A Cost Savings Over Microchip's Traditional User Programmed Devices (EPROM, EEPROM). ROM Devices (PIC16CR8X) Do Not Allow Serializati 1th, 2024

### **PIC16CE62X OTP 8-Bit CMOS MCU With EEPROM Data Memory**

1999 Microchip Technology Inc. DS40182C-page 3 PIC16CE62X 1.0 GENERAL DESCRIPTION The PIC16CE62X Are 18 And 20-Pin EPROM-based Members Of The Versatile PICmicro ® Family 2th, 2024

## **EEPROM Emulation For Gen 2 C2000 Real-Time MCUs (Rev. A)**

Figure 4-1 Shows The Directory Structure Of The Generation 2 C2000 MCUs\_EEPROM Directory. Figure 4-1. F28xxx\_EEPROM Directory Structure As Shown, Each F28xxx Generation Has Its Own Folder That Contains Subfolders. The Flash API And Header Files For Each Generation Are Provided. The Example 3th, 2024

## **CE27 EEPROM PROGRAMMING SOFTWARE REFERENCE MANUAL**

The CE27 Is Used To Program The VXR-7000 Desktop Repeater. With The CE27 Programming Software, You Can Quickly And Easily Program The Vertex VXR-7000 Repeater's Channels And Configuration From Your Personal Computer. In The Event Of An Accidental Memory Failure, Re-peater Memory And Co 2th, 2024

## **D2XX EEPROM Programming Examples - FTDI**

FTDI's D2XX Drivers Allow For Users To Read And Program The EEPROM Directly. Refer To D2XX Programmer's Guide Section 4 EEPROM Programming Interface Functions. The D2XX Drivers Should Be Installed On The PC For These Examples To



Work. These Programming Functions Could Be Used In A Production Environment.  
1.2 Scope 2th, 2024

There is a lot of books, user manual, or guidebook that related to Serial Eeprom  
Cross Reference Guide PDF in the link below:

[SearchBook\[MjAvMjE\]](#)